



**GENERAL DIMENSIONS**

MODEL	L	H	W	HEX	RADIUS	TORQUE (ft. lb)	
	(Inch)	(Inch)	(Inch)	(Inch)	(Inch)	Min	Max
STEALTH-2	5.53	4.21	1.25	1-1/4 ~ 2-3/8	1.08 ~ 1.73	280	1,860
STEALTH-4	6.58	5.43	1.66	1-1/2 ~ 3-1/8	1.41 ~ 2.30	600	4,020
STEALTH-8	8.00	6.40	2.08	2-1/8 ~ 3-7/8	1.85 ~ 2.87	1,175	7,910
STEALTH-14	9.33	7.94	2.50	2-7/8 ~ 4-5/8	2.41 ~ 3.44	2,015	13,430

**LINK SIZE & RADIUS**

STEALTH-2		STEALTH-4		STEALTH-8		STEALTH-14	
HEX	RADIUS	HEX	RADIUS	HEX	RADIUS	HEX	RADIUS
to 1-1/8"	1.00"	to 1-7/16"	1.30"	to 2"	1.74"	to 2-3/4"	2.30"
to 1-1/4"	1.08"	to 1-5/8"	1.41"	to 2-3/16"	1.85"	to 2-15/16"	2.41"
to 1-7/16"	1.18"	to 1-13/16"	1.52"	to 2-3/8"	1.96"	to 3-1/8"	2.53"
to 1-5/8"	1.29"	to 2"	1.63"	to 2-9/16"	2.07"	to 3-3/8"	2.65"
to 1-13/16"	1.40"	to 2-3/16"	1.74"	to 2-3/4"	2.18"	to 3-1/2"	2.75"
to 2"	1.51"	to 2-3/8"	1.85"	to 2-15/16"	2.30"	to 3-3/4"	2.88"
to 2-3/16"	1.62"	to 2-9/16"	1.96"	to 3-1/8"	2.41"	to 3-7/8"	2.98"
to 2-3/8"	1.73"	to 2-3/4"	2.07"	to 3-3/8"	2.53"	to 4-1/8"	3.10"
to 2-9/16"	1.84"	to 2-15/16"	2.18"	to 3-1/2"	2.64"	to 4-1/4"	3.21"
		to 3-1/8"	2.30"	to 3-3/4"	2.76"	to 4-5/8"	3.44"
				to 3-7/8"	2.87"		



**HYTORC®**  
*Hands-Off Bolting,  
 Hands-On Service!™*